

SIAT


MAILLIS

S8-SK1

Semi Automatic Carton Sealers



Taping unit K11R



Aluminium telescopic legs

CE

for more details:



S8




SK1


S8 and SK1 models are semi-automatic sealing machines with manual adjustment. Easy to use and simple to adjust, they enable to start the production in just minutes. Thanks to the side drive belts and the K11R or K12R taping units, they allow the perfect sealing of the box.

The machines have been designed in compliance with CE regulations.

> SK1



> S8



other languages: www.siat.com



> Machine dimensions
Dimensioni macchina
Machinmessungen
Dimensions de la machine
Dimensiones de máquina

Size / Weight packaging			LxWxH
> S8 / S8/4	130	160	106x100x118
> SK1	160	175	114x78x115


> SK1

	Min.	Max
L	1080	-
W	690	-
H	1260	1600
cbh	485	825
AS 77	585	925
AS 80	685	1025


> S8

	Min.	Max
L	975	-
W	900	-
H	1260	1600
cbh	485	825
AS 77	585	925
AS 80	685	1025

> Taping units
Unità nastranti
Verschliesseinheiten
Unités enrubanueuses
Unidades de precinto



> Box dimensions
Dimensioni delle scatole
Kartonabmessungen
Dimensions des boîtes
Dimensiones de cajas



> SK1

	K11R	
	Min.	Max
l	150	∞
w	140	500
h	100	500

> S8 - S8/1

	K11R std. / K12R on demand	
	Min.	Max
l	150	∞
w	150	500
h	100	500

	K11R/ K12R	
	mm	
A	410 Max	
B	50 / 75	
C	76	


> S8/4

	K11R	
	Min.	Max
l	150	∞
w	105	500
h	90	500

> S08

	K11R std. / K12R on demand	
	Min.	Max
l	150	∞
w	120	500
h	50	n.n.

> Production capacity
Capacità di produzione
Produktionskapazität
Capacité de production
Capacidad de producción




> SK1	Bph
Max pcs.*	1200

> S8	Bph
Max pcs.*	1200

> S8/4	Bph
Max pcs.*	1200

* Always based on shorter manageable box

> Standard voltage
Votaggio standard
Standardspannung
Tension standard
Voltaje estándar



> SK1

380/400V - 50Hz - 3F	
440V - 60Hz - 3F	
Amps	1,54
Power kW	0,13
Phase	3Ph + PE

> S8

380/400V - 50Hz - 3F	
440V - 60Hz - 3F	
Amps	1
Power kW	0,18
Phase	3Ph + PE

> S8/4


380/400V - 50Hz - 3F	
440V - 60Hz - 3F	
Amps	1
Power kW	0,18
Phase	3Ph + PE

> Optionals
Accessori
Zubehör
Accessories
Accesorios

> AS80
Higher legs
Set gambe più alte
Höhere Stützen
Pieds plus hauts
Patas más altas




> AS77
Casters
Set ruote
Rädchen
Roulettes
Ruedas



> RG
Roller conveyor
Piani a rulli
Rollenbahnen
Plans à rouleaux
Rodillos libres



> GTL - GTR
Extendable conveyor
Rulliera estensibile
Ausziehbare rollenbahnen
Convoyeur extensible
Rodillos extensibles



> K-125 / K-250
Inkjet printer
Stampante ad inchiostro
Tintenstrahldrucker
Marqueur à jet d'encre
Impresora de inyección de tinta

